



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
14.12.2005 Bulletin 2005/50

(51) Int Cl.7: **A61B 17/80**

(21) Application number: **05012522.8**

(22) Date of filing: **10.06.2005**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR
 Designated Extension States:
AL BA HR LV MK YU

(72) Inventors:
 • **Leung, Takkwong Ross**
Piscataway New Jersey 08854 (US)
 • **Waliluk, Stephen**
Phillipsburg New Jersey 08865 (US)
 • **Bailey, Kirk**
Blairstown New Jersey 07825 (US)

(30) Priority: **10.06.2004 US 865248**

(71) Applicant: **EBI, L.P.**
Parsippany, New Jersey 07054 (US)

(74) Representative: **Duxbury, Stephen et al**
Arnold & Siedsma
Isartorplatz 5
80331 München (DE)

(54) **Bone plating system**

(57) A plating system for bone includes a plate member. The plate member has a top surface and a bottom surface. A plurality of holes are defined by the plate member. Each of the holes extend between the top surface and the bottom surface along an axis. At least a

first hole of the plurality of holes is a threaded hole and has a first dimension generally perpendicular to the axis and a second dimension generally perpendicular to the axis. The first dimension is greater than the second dimension.




FIG - 1

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

FIELD OF THE INVENTION

[0001] The present invention relates generally to orthopedic surgical procedures. More particularly, the present invention relates to a bone plating system.

BACKGROUND AND SUMMARY OF THE INVENTION

[0002] In certain orthopedic surgical procedures, it is necessary to secure multiple bones or bone portions relative to each other to facilitate proper healing. For example, it is frequently necessary to secure two or more portions of a broken long bone such as the tibia to ensure proper healing. This need may be the result of physical trauma from fractures or dislocations, degenerative diseases, or tumors. Improper mending of the bone may result in deformity, discomfort or both.

[0003] Common methods of fracture treatment include casting and external fixation. It is also well known to treat fractures with internal plating systems. Use of such plating systems involves the attachment of a plate to the bone with bone screws. The plating systems function to stabilize discrete bone portions and thereby facilitate fusion of the bone portions in a particular orientation for healing or to repair a condition of the patient.

[0004] Various plating systems are known. One known plating system is shown in German utility model DE 93 21 544 U1. This German utility model illustrates a plating system having a plate member with a shaft portion and a head portion. The head portion is configured to conform to a metaphysis of a bone and includes a plurality of internally threaded holes. The threads of the holes engage threaded heads of bone screws. The shaft portion is shown to include two round holes and an elongated slot. The holes and slot of the shaft portion are unthreaded for receiving bone screws with unthreaded heads.

[0005] It remains desirable to continuously improve the pertinent art.

[0006] The present invention relates to a plating system for bone. The plating system includes a plate member having a top surface and a bottom surface. A plurality of holes are defined by the plate member. Each of the holes extend between the top surface and the bottom surface along an axis. At least a first hole of the plurality of holes is a threaded hole and has a first dimension generally perpendicular to the axis and a second dimension generally perpendicular to the axis. The first dimension is greater than the second dimension.

[0007] In another aspect, the present invention relates to a plating system for bone having a plate member defining at least one spherically threaded hole. The plate member has a top surface and a bottom surface. A plurality of holes are defined by a plate member. Each

of the holes extends between the top surface and the bottom surface. A first hole of the plurality of holes is spherical. The plating system further includes a first bone screw having a shaft extending below the plate member and a head disposed in the first hole. The head of the first bone screw is spherical.

[0008] Additional advantages and further areas of applicability of the present invention will become apparent from the detailed description and appended claims provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0010] Figure 1 is a top view of a plating system according to the present invention.

[0011] Figure 2 is a cross-sectional view taken along the line 2-2 of Figure 1.

[0012] Figure 3 is a cross-sectional view taken along the line 3-3 of Figure 1.

[0013] Figure 4 is a cross-sectional view taken along the line 4-4 of Figure 1.

[0014] Figure 5 is a cross-sectional view similar to Figure 4, the bone screw shown angulated from the orientation illustrated in Figure 4.

[0015] Figure 6 is a cross-sectional view taken along the line 6-6 of Figure 1.

[0016] Figure 7 is a cross-sectional view similar to Figure 3A, illustrating a bone screw with an unthreaded head.

[0017] Figure 8 is a cross-sectional view similar to Figure 6, illustrating a collar formed with threads to engage the threads of the plate member.

[0018] Figure 9 is a cross-sectional view similar to Figure 3, illustrating the first bone screw angulated relative to the plate member.

DETAILED DESCRIPTION OF EMBODIMENTS

OF THE PRESENT INVENTION

[0019] The following description of embodiments of the present invention will be understood to be merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

[0020] With reference to Figures 1 through 9 of the drawings a bone plating system constructed in accordance with the teachings of the present invention is illustrated and generally identified at reference character 10. In certain applications, the teachings of the present invention are specifically intended for a plating system that can be used to stabilize bone portions of the prox-

imal femur, distal tibia and proximal tibia, for example. It will become apparent to those skilled in the art, however, that the teachings of the present invention are also suitable for various other applications in which surgical repair of bone with a plate is desired. Other applications include but are not limited to the distal radius and the spine.

[0021] The bone plating system 10 is illustrated to generally include a plate member 12. The plate member 12 may be flat or may be contoured for specific applications in a manner well known in the art to conform with a bone. The plate member 12 is generally shown to include an upper surface 14 and a lower surface 16. The plate member 12 may be constructed of any suitable biocompatible material. One exemplary material is a titanium alloy such as Ti6Al4V. Other materials having acceptable strength characteristics, including but not limited to stainless steel, may also be employed.

[0022] The plate member 12 defines a thickness t between the upper surface 14 and the lower surface 16. The thickness t may be constant throughout the plate member 12 or may be variable. In one particular application in which the plate member 12 is constructed of Ti6Al4V and intended for stabilizing the proximal tibia, the plate member 12 has an approximate thickness between 2.0 and 5.0 mm. More preferably, this particular plate member 12 has a thickness of approximately 2.0 mm. In another particular application, in which the plate member 12 is constructed of stainless steel and intended for stabilizing the distal radius, the plate member 12 has an approximate thickness between 1.5 and 2.0 mm, and more preferably has a thickness of approximately 1.5 mm. It should be readily apparent that the plate thickness t may vary according to material choices and strength requirements.

[0023] The plate member 12 is illustrated to define a plurality of holes 18 for receiving bone screws 20 for securing the plate member 12 to a bone (not specifically shown). For purposes of illustration, the plate member 12 is shown in Figure 1 to include three holes 18. It will be understood that the particular number of holes 18 defined by the plate member 12 and the specific types of holes 18 may vary within the scope of the present invention and largely depend on the intended application for the plating system 10.

[0024] With particular reference to Figures 1-3, the plurality of holes 18 defined by the plate member 12 includes a first hole 18A. The first hole 18A is an elongated hole and is shown in the cross-sectional views of Figures 2 and 3 receiving a first bone screw on fastener 20A of the plurality of bone screws 20. The bone screw 20A has a longitudinal axis A_1 oriented in Figures 2 and 3 generally perpendicular to a plane defined by the plate member 12. The first bone screw 20A is shown to include a threaded shaft for engaging bone. Insofar as the present invention is concerned, the shaft of the bone screws 20 are conventional in construction.

[0025] The first hole 18A extends between the top sur-

face 14 and the bottom surface 16 in the direction of the axis A_1 (as shown in Figure 2, for example). Given the particular orientation of the bone screw 20A, the axis A_1 is coincident with a longitudinal axis of the bone screw 20A. The first hole 18A has a first dimension D_1 adjacent the upper surface 14 in a first direction generally perpendicular to the axis A_1 . The first hole 18A includes a second dimension D_2 adjacent the upper surface 14 in a second direction generally perpendicular to the axis A_1 . The first dimension D_1 is substantially greater than the second dimension D_2 . In the embodiment illustrated, the first hole 18A is elongated along the length of the plate member 12 and the first and second dimensions D_1 and D_2 correspond to a length and a width of the hole 18A, respectively. In one particular application, the first dimension D_1 is approximately 7.25 mm and the second dimension D_2 is approximately 10.0 mm.

[0026] As shown, particularly in Figures 2 and 3, the plate member 12 is threaded. More particularly, the plate member 12 is shown to include at least one ridge 22 in the first hole 18A extending completely about an inner circumference. The plate member 12 may include a plurality of ridges 22. In the embodiment illustrated, the ridges 22 are formed parallel to one another and are each oriented generally parallel to the plane defined by the plate member 12. The minor diameters of the ridges 22 define an effective opening having a circular shape.

[0027] The circular ridges 22 are configured to cooperate with a spherically shaped head of a bone screw. For example, the first bone screw 20A, which is shown particularly in Figures 2 and 3, is illustrated to include a spherically shaped threaded head 24 for engaging the ridges 22. Engagement of the threaded head 24 with the ridges 22 functions to orient the bone screw 20A relative to the plate member 12 and to fix the bone screw 20A relative to the plate member 12. Given the orientation of the circular ridges, the bone screw 20A is resultingly oriented with its longitudinal axis A_1 generally perpendicular to the plane defined by the plate member 12. In the embodiment illustrated, the head 24 of the first bone screw 20A includes a double lead thread 26. Alternatively, the ridges 22 of the plate member 12 can be replaced with a helical thread (not shown with respect to the first hole 18A) for threadably engaging the head 24.

[0028] In certain applications, it may be desired to orient the ridges 22 at an angle relative to the plane of the plate member 12. In such alternative applications, the bone screws 20A would correspondingly be fixed to the plate member 12 at an angle. For example, certain applications may require convergence of two or more bone screws 20 at fixed angles.

[0029] As shown in the cross-sectional view of Figure 7, the first hole 18A is also particularly adapted to receive a second bone screw 20B having a head 28 without threads. The head 28 of the second bone screw 20B is generally spherical in the shape. This spherical shape of the head 28 cooperates with the ridges 22 to allow the second bone screw 20B to angulate relative to the

plate member 12. In this regard, as compared to the fixed relationship established with the threaded head 28 of the first bone screw 20A (as shown in Figures 2 and 3) the second bone screw 20B can be engaged with the bone at a variable angle.

[0030] The elongated shape of the first hole 18A provides a surgeon with increased flexibility for bone screw placement. In this regard, the surgeon may position the bone screw 20A or 20B anywhere along the length of the first hole 18A in a direction parallel to the first dimension D_1 . This flexibility in positioning of bone screws 20A or 20B relative to the plate member 12 is available regardless of whether the surgeon elects to use a bone screw 20A having a threaded head 24 for establishing a fixed relationship between the plate member 12 and the bone screw 20A at a predetermined angle, or a bone screw 20B having an unthreaded head 28 that allows angulation relative to the plate member 12.

[0031] The elongated shape of the first hole 18A additionally allows the surgeon to compress a fracture of the bone by translating the bone screw 20 along the hole 18A in a direction parallel to D_1 . The circular ridges 22 permit such translation even where a threaded head is used, thereby retaining the locking relationship between the plate member 12 and the bone screw 20. Translation of the bone screw 20 is manually accomplished with an insertion tool (e.g., screw driver) that engages the head. Explaining further, the surgeon linearly advances the screw 20 along the hole 18A with the insertion tool. In certain alternative applications, it may be desirable to automatically compress the bone by angling the ends of the hole 18A. In such applications, a non-threaded head of a bone screw 20 would engage an end of the hole 18A and compress the bone as the non-threaded head transitions past the angled end of the hole 18A.

[0032] With particular reference to the cross-sectional view of Figure 4, a second hole defined by the plate member 12 is illustrated. As compared to the first hole 28, the second hole 20B is generally circular in shape. The hole 20B has an upper diameter D_3 at the upper surface 14 of the plate member 12 and a smaller diameter D_4 at the lower surface 16 of the plate member 12. Between the upper surface 14 and the lower surface 16 the second hole 20B includes a spherically shaped portion 30 having a plurality of threads 32. Alternatively, it will be understood that the plate member 12 can be formed with a plurality of circular ridges similar to the ridges 22 shown and described in connection with the first hole 18A.

[0033] Figures 4 and 5 illustrate the second hole 20B operatively associated with a bone screw 20B identical to the bone screw 20B discussed above. Figure 4 illustrates the second bone screw 20B with its longitudinal axis oriented generally perpendicular to the plane defined by the plate member 12 immediately prior to seating of the spherical head 28 on the threads 32. Figure 5 illustrates the bone screw 20B seated with its spherical head 28 seated on the threads 32 and the bone screw

20B with its longitudinal axis articulated from the perpendicular orientation shown in Figure 4. It will be appreciated that the spherical shape of the head and the cooperating shape of the threads 32 allow the bone screw 20B to articulate from the orientation shown in Figure 4 approximately 15° in any direction.

[0034] With particular reference to the cross-sectional view of Figure 6, a third hole 20C defined by the plate member 12 is illustrated. It will be understood that the third hole 20C and the threads 32 associated with the third hole 20C are identical to the second hole 20B and corresponding threads 32 discussed above. The third hole 20C is illustrated with a bone screw 20A having a threaded head 24. The bone screw 20A is identical to the bone screw 20A discussed above. In the manner discussed above, the threaded head 24 and the threaded hole 20C cooperate for fixedly securing the bone screw 20A to the plate member 12. The bone screw 20A is secured to the plate with the longitudinal axis A_1 of the bone screw 20A oriented generally perpendicular to the plane defined by the plate member 12.

[0035] Turning to Figure 8, the third hole 18C of the plate member 12 is shown operatively associated with a third bone screw 20C. The third bone screw 20C is illustrated to include a threaded shaft portion 36 for threadably engaging a bone and a head portion 38. The third bone screw 20C is further shown to include a collar 40. The collar 40 defines an aperture 42 for receiving the head 38 of the third bone screw 20C. The collar 40 further includes an outer threaded surface 44 which is spherical in shape. The outer threaded surface 44 cooperates with the threads 32 of the hole 18C substantially in the manner discussed above with respects to Figure 6. The collar 40 maintains a locking connection with the plate member 12 while allowing the plate member 12 to be drawn adjacent the bone. In this manner, the profile of the plate member 12 may be minimized.

[0036] With particular reference to Figure 8, a cross-sectional view similar to Figure 3 is illustrated. In Figure 8, however, the bone screw 20A is angled from a perpendicular orientation. Such angulation of the bone screw 20A is permitted despite the threaded engagement between the head and the plate member 12 due to the double-lead thread of the head and the circular ridges 22 of the plate member 12.

[0037] In the embodiment illustrated, the double lead thread and the ridges 22 allow for angulation in increments of approximately 5° to 10° from the perpendicular orientation of Figure 3.

[0038] The teachings of the present invention have now been described to include various types of plate member holes and various types of bone screws. It is readily anticipated that the different holes and different bone screws can be combined alternatively for particular applications. Further in this regard, it is anticipated that certain applications may only include one type of hole. For example, a plate member may be constructed to include all elongated holes 18A. It is further anticipated

ed that the various teachings of the present invention may be utilized separately in any combination to stabilize both long bones (including but not limited to the femur, the tibia, and the radius) and vertebral bodies.

[0039] The description of the invention is merely exemplary in nature and, thus, variations that do not depart from the gist of the invention are intended to be within the scope of the invention. Such variations are not to be regarded as a departure from the spirit and scope of the invention.

Claims

1. A plating system for bone, the plating system comprising:

a plate member having a top surface and a bottom surface; and
a plurality of holes defined by the plate member extending between the top surface and the bottom surface along a hole axis, at least a first hole of the plurality of holes having threads extending completely about an inner circumference, the first hole having a first dimension generally perpendicular to the hole axis and a second dimension generally perpendicular to the hole axis, the first dimension being greater than the second dimension.

2. The plating system for bone of Claim 1, wherein the first hole includes at least one ridge extending completely about the inner circumference.

3. The plating system for bone of Claim 2, wherein the first hole includes a plurality of circular ridges extending completely about the inner circumference.

4. The plating system for bone of Claim 1, further comprising a bone screw threadably engaging the first hole.

5. The plating system for bone of Claim 4, wherein the bone screw includes a collar threadably engaging the first hole.

6. The plating system for bone of Claim 4, wherein the bone screw includes a head threadably engaging the first hole.

7. The plating system for bone of Claim 2, further comprising a bone screw having a head, the head including a double lead thread engaging the at least one ridge.

8. The plating system for bone of Claim 2, further comprising a bone screw having an unthreaded head, the at least one circular groove matingly receiving

the unthreaded head.

9. The plating system for bone of Claim 8, wherein the unthreaded head is at least partially spherical and allows angulation of the bone screw relative to the plate member.

10. The plating system for bone of Claim 7, wherein the at least one ridge is oriented generally perpendicular to the axis and the bone screw has a longitudinal axis angled relative to the hole axis.

11. A plating system for bone, the plating system comprising:

a plate member having a top surface and a bottom surface; and
a plurality of holes defined by the plate member each extending between the top surface and the bottom surface, a first hole of the plurality of holes being spherical; and
a first bone screw having a shaft extending below the plate member and a head disposed in the first hole, the head being spherical.

12. The plating system for bone of Claim 11, wherein the spherical shape of the first hole is defined by a thread.

13. The plating system for bone of Claim 11, wherein the first hole is helically threaded.

14. The plating system for bone of Claim 12, wherein the head of the first bone screw is unthreaded and the screw is articable relative to the plate member, the first screw being seated on a minor diameter of the first hole.

15. The plating system for bone of Claim 12, wherein the head of the first screw threadably engages the first hole to lock the first screw relative to the plate member.

16. The plating system for bone of Claim 11, wherein the head includes a modular collar.

17. The plating system for bone of Claim 16, wherein the modular collar threadably engages the first hole.

18. A plating system for bone, the plating system comprising:

a plate member having a top surface and a bottom surface;
a hole defined by the plate member extending between a top surface and a bottom surface along a hole axis, the hole including at least one circular ridge extending completely about an in-

ner circumference; and
a fastener threadably engaging the at least one
ridge.

19. The plating system for bone of Claim 18, wherein 5
the hole includes a plurality of ridges.

20. The plating system for bone of Claim 18, wherein
the at least one ridge is oriented generally perpen-
dicular to the axis and the bone screw has a longi- 10
tudinal axis angled relative to the hole axis.

15

20

25

30

35

40

45

50

55




FIG - 1






FIG - 2







FIG - 7





FIG - 8




FIG - 9



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 05 01 2522

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	DE 203 17 651 U1 (AAP IMPLANTATE AG) 11 March 2004 (2004-03-11)	1-4, 6-15, 18-20	A61B17/80
Y	* the whole document *	16	
Y	----- US 2001/014807 A1 (WAGNER ERIK J ET AL) 16 August 2001 (2001-08-16)	16	
A	* paragraph [0057] - paragraph [0058]; figure 9 *	5,17	
A	----- US 6 730 091 B1 (PFEFFERLE JOACHIM ET AL) 4 May 2004 (2004-05-04) * column 10, line 6 - line 34; figures 7,8 *	1-20	

			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A61B
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
Berlin		19 September 2005	Olsson, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

1
EPO FORM 1503 (3.02.02) (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 05 01 2522

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-09-2005

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 20317651	U1	11-03-2004	NONE	

US 2001014807	A1	16-08-2001	NONE	

US 6730091	B1	04-05-2004	AT 286678 T	15-01-2005
			AU 3954200 A	17-11-2000
			WO 0066012 A1	09-11-2000
			DE 50009225 D1	17-02-2005
			EP 1175181 A1	30-01-2002
			JP 2002542875 T	17-12-2002

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82